

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in this application:

LISTING OF CLAIMS:

Claims 1 to 16. (Canceled).

17. (Currently Amended) A handheld measuring device for localizing at least one object enclosed in a medium, comprising:

at least one photometric sensor that obtains a first measurement signal of ~~[[an]]~~ the at least one object to be examined, wherein by evaluation of the measurement signal, information about ~~[[an]]~~ the at least one object enclosed in the medium is obtained; and

at least one further sensor for generating at least one further second measurement signal for obtaining information about the at least one object enclosed in the medium, wherein at least one sensor is optimized on the basis of information obtained from the other sensors; and

~~a display that depicts signal characteristics detected by a displacement sensor.~~

18. (Previously Presented) The measuring device of claim 17, wherein the at least one photometric sensor includes an infrared sensor.

19. (Previously Presented) The measuring device of claim 17, wherein the at least one further sensor includes a radar sensor.

20. (Previously Presented) The measuring device of claim 19, wherein the radar sensor includes a broadband sensor of a pulsed radar.

21. (Previously Presented) The measuring device of claim 17, wherein the at least one further sensor includes an inductive sensor.

22. (Previously Presented) The measuring device of claim 17, wherein the at least one further sensor includes a capacitive sensor.

23. (Previously Presented) The measuring device of claim 22, wherein the at least one further capacitive sensor includes a high-frequency capacitive sensor that, by measuring an impedance of its electrodes, obtains information about objects enclosed in the medium.

24. (Previously Presented) The measuring device of claim 17, wherein at least two of the sensors are integrated into a common housing of the measuring device.

25. (Previously Presented) The measuring device of claim 24, wherein at least two of the sensors are disposed on a common circuit board.

26. (Withdrawn) A method for localizing at least one object enclosed in a medium, the method comprising:

- generating a measurement signal by at least one photometric sensor;
- evaluating the measurement signal to obtain information about an object enclosed in the medium;
- evaluating at least one further measurement signal to obtain information about the object enclosed in the medium;
- determining the desirability of the signals for subsequent data processing; and
- selectively displaying the desired information of at least one of the sensors.

27. (Withdrawn) The method of claim 26, wherein the at least one further measurement signal is generated by at least one further sensor apparatus.

28. (Withdrawn) The method of claim 26, wherein the at least one first measurement signal and the at least one second measurement signal are measured in a parallel fashion.

29. (Withdrawn) The method of claim 26, wherein the at least one first measurement signal and the at least one second measurement signal are measured in a quasi-parallel fashion.

30. (Withdrawn) The method of claim 26, wherein the at least one first measurement signal and the at least one second measurement signal are measured in a serial fashion.

31. (Withdrawn) The method of claim 26, wherein the measurement signals of a plurality of sensors are measured and evaluated, the sensors deriving from a group encompassing at least capacitive sensors, inductive sensors, and photometric sensors.

32. (Withdrawn) The method of claim 26, wherein at least one measurement signal of a sensor is optimized by evaluating at least one further measurement signal.

33. (Withdrawn) The method of claim 26, wherein the at least one photometric sensor includes an infrared sensor.

Claim 34. (Canceled).

35. (Previously Presented) The measuring device of claim 17, further comprising a circuit that activates a predefined search routine.

36. (Currently Amended) The measuring device of claim 17, wherein the measuring device is adapted to: ~~perform the method according to claim 26.~~

generate a measurement signal by at least one photometric sensor;

evaluate the measurement signal to obtain information about an object enclosed in the medium;

evaluate at least one further measurement signal to obtain information about the object enclosed in the medium;

determine the desirability of the signals for subsequent data processing; and

selectively display the desired information of at least one of the sensors.

37. (Withdrawn - Currently Amended) The method according to claim 26, wherein the method is performed using ~~the device according to claim 17~~ a handheld

measuring device for localizing at least one object enclosed in a medium, the device including:

at least one photometric sensor that obtains a first measurement signal of the at least one object to be examined, wherein by evaluation of the measurement signal, information about the at least one object enclosed in the medium is obtained;
and

at least one further sensor for generating at least one further second measurement signal for obtaining information about the at least one object enclosed in the medium, wherein at least one sensor is optimized on the basis of information obtained from the other sensors.